

<b>Product Name :</b> Break Drum Friction	<b>Product Code :</b> ASTRALAB-SUPPLYA119002
----------------------------------------------	-------------------------------------------------



<b>Description :</b>
Break Drum Friction
<b>Technical Specification :</b>
An aluminium brake drum is secured to one end of a sturdy bench top mounted base.
The drum has an external cord grooved and its inside face is machined to plain aluminium.
A cord is wrapped around the perimeter of the brake drum and the free end of the cord runs over a pulley at the other end of the base and terminates with a load hanger.
Torque is applied to the brake drum by using the calibrated weights set provided and the load hanger.
Mounted inside the brake drum is a single brake shoe with its own pivot.
A second cord connects to the brake shoe and again runs over a pulley and terminates at the load hanger.
As the load is applied to the brake shoe the friction force increases.

The student then add load to the torque hanger to try and rotate the brake drum at near constant speed.

The sense of rotation of the torque determines whether the single brake shoe acts as a leading or trailing shoe

Aluminium brake drum

Industry standard brake shoes

Length: 0.400m.

Width: 0.200m.

Height: 0.200m.



## Astra Scientific

www.astrascientific.com, **Email:** info@astrascientific.com

**Address:** K-88, 20th Street, Annanagar, Chennai, India – 600040 **Phone:** +91-8860605265