

Product Name :
Vane Shear Test Apparatus

Product Code :
ASTSOIL-0032



Description :

Vane Shear Test Apparatus

Technical Specification :

Specification:

The apparatus is designed for conducting in situ vane shear test from bottom of a bore hole in saturated cohesive deposits for determining their in place shearing resistance.

The equipment consists of a torque applicator assembly mounted on a base, a gear wheel, which is marked in degrees, holds a torque ring and is geared to a crank, the torque ring is a split ring & deforms as torque is applied & the deformation is indicated by a dial gauge. A calibration chart to convert dial gauge readings to torque force in kgs/cm² is supplied. A pointer is provided.

For registering the rotations of the vane, a detachable stand is provided to anchor the instrument an attachment to securely hold the string of rods is provided the equipments comprises of the following :

Torque applicator assembly capacity 2000kg/cm² with split proving ring

& dial gauge 0.002 x 5mm complete with stand.

Vane (with vane rod) 37.5mm dia x 75mm high : 1 no.

Vane (with vane rod) 50.0mm dia x 100mm high : 1 no.

Torque rod (square cross section) 0.6mts long : 1 no.

Rods quick couplind type, 1 mtr. long : 1 no.

Rods quick coupling type, 1 ½ mtr. long : 1 no.

Dummy rod, corresponding to 37.5mm dia vane : 1 no.

Dummy rod , corresponding to 50.0mm dia vane : 1 no.



Astra Scientific

www.astrascientific.com, **Email:** info@astrascientific.com

Address: K-88, 20th Street, Annanagar, Chennai, India – 600040 **Phone:** +91-8860605265